

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

#### MANUFACTURER

ITW Polymers Sealants North America  
 12271 Monarch St.  
 Garden Grove, CA 92841

**Product Stewardship:** (714) 898-0025

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

**COMMENTS:** PACIFIC POLYMERS and Elasto-Poxy are a registered trademarks of Illinois Tool Works, Inc.

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Skin Corrosion, Category 1B  
 Serious Eye Damage, Category 1  
 Target Organ Toxicity (Single exposure), Category 3  
 Skin Sensitization, Category 1  
 Acute Toxicity (Oral), Category 4  
 Acute Toxicity (Inhalation), Category 1  
 Acute Toxicity (Dermal), Category 4

#### GHS LABEL



Exclamation  
mark



Corrosion



Health  
hazard

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H335: May cause respiratory irritation.  
 H314: Causes severe skin burns and eye damage.  
 H318: Causes serious eye damage.  
 H317: May cause an allergic skin reaction.  
 H302: Harmful if swallowed.  
 H312: Harmful in contact with skin.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

[201]: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.  
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233: Keep container tightly closed.  
 P240: Ground and bond container and receiving equipment.  
 P243: Take action to prevent static discharges.  
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

P264: Wash thoroughly after handling.  
 P271: Use only outdoors or in a well-ventilated area.  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P284: [In case of inadequate ventilation] wear respiratory protection.

### Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P302+P352: IF ON SKIN: Wash with plenty of water.  
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312: Call a POISON CENTER/doctor if you feel unwell.  
 P314: Get medical advice/attention if you feel unwell.  
 P331: Do NOT induce vomiting.  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313: If eye irritation persists: Get medical advice/attention.  
 P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
 P362: Take off contaminated clothing.  
 P370+P378: In case of fire: Use appropriate media to extinguish.  
 P391: Collect spillage.

### Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235: Store in a well-ventilated place. Keep cool.  
 P405: Store locked up.

### Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

## EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS:** WARNING! Irritant. May cause respiratory tract, eye, and skin irritation.

### POTENTIAL HEALTH EFFECTS

**EYES:** Causes severe skin and eye burns.

**SKIN:** May cause mild to moderate skin irritation. Symptoms may include redness and burning of the skin.

**INGESTION:** Not likely route of entry. Harmful if swallowed, may cause nausea. Consult a physician.

**INHALATION:** May cause nose, throat and lung irritation. Inhalation of vapors and/or aerosols in high concentrations may cause irritation of respiratory system such as a sore throat. Harmful if inhaled.

**MEDICAL CONDITIONS AGGRAVATED:** Skin disorders and allergies

**ROUTES OF ENTRY:** Eye and Skin Contact, Inhalation and Ingestion

**IRRITANCY:** Eyes, nose, throat, respiratory tract, and skin irritation.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Wt. % | CAS |
|---------------|-------|-----|
|---------------|-------|-----|

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

|             |      |         |
|-------------|------|---------|
| Polyamines  | < 50 | Mixture |
| Acetic Acid | < 1  | 64-19-7 |

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

**INGESTION:** Do not induce vomiting, keep person warm, quiet and get medical attention immediately. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Liquid and vapor can severely irritate the eyes depending on type of exposure (splash, vapor) and exposure time.

**SKIN:** Mild to moderate skin irritant.

**INGESTION:** Not likely route of entry. May cause nausea and vomiting if ingested.

**INHALATION:** High vapor concentrations may cause CNS depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion, and unconsciousness.

**ACUTE EFFECTS:** High vapor concentrations may cause central nervous system (CNS) depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion and unconsciousness.

**CHRONIC EFFECTS:** Prolonged or repeated exposure may cause allergic reaction/sensitization, asthma, and eczema.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Class IIIB

**GENERAL HAZARD:** Combustible Liquid.

**EXTINGUISHING MEDIA:** Foam, dry chemical, carbon dioxide, water spray or fog.

**EXPLOSION HAZARDS:** No known unusual hazards in a fire/explosion situation.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

**SENSITIVITY TO IMPACT:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from firefighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Burning produces obnoxious and toxic fumes. Downwind personnel should be evacuated in case of large fires.

### 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Vapors may be heavier than air and will collect in low areas. Containers may be hazardous when empty.

**HANDLING:** Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

**STORAGE:** Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

**STORAGE TEMPERATURE:** 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

**SHELF LIFE:** 1 year from manufacture date

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

### EXPOSURE GUIDELINES

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) |                  |             |            |                   |
|---|------------------|-------------|------------|-------------------|
| EXPOSURE LIMITS                             |                  |             |            |                   |
| Chemical Name                               | Type             |             | ppm        | mg/m <sup>3</sup> |
| Polyamines                                  | <b>OSHA PEL</b>  | <b>TWA</b>  | NL [1]     | NL [1]            |
|   |                  | <b>STEL</b> | NL [1]     | NL [1]            |
|   | <b>ACGIH TLV</b> | <b>TWA</b>  | NL [1]     | NL [1]            |
|   |                  | <b>STEL</b> | NL [1]     | NL [1]            |
| Acetic Acid                                 | <b>OSHA PEL</b>  | <b>TWA</b>  | 10 ppm [1] | 25 mg/m3 [1]      |
|   |                  | <b>STEL</b> | NL         | NL                |
|   | <b>ACGIH TLV</b> | <b>TWA</b>  | 10 ppm     | 25 mg/m3          |
|   |                  | <b>STEL</b> | 15 ppm     | 37 mg/m3          |

**Footnotes:**  
 1. NL = Not Listed

**ENGINEERING CONTROLS:** Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) or a full face respirator.

**SKIN:** Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**PROTECTIVE CLOTHING:** Wear chemical resistant gloves, such as nitrile rubber.

**WORK HYGIENIC PRACTICES:** Use good hygiene practices when handling this material. Wash hands thoroughly after use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**ODOR:** Ammonia Odor

**ODOR THRESHOLD:** Not Determined

**COLOR:** Yellowish

**pH:** Not Determined

**PERCENT VOLATILE:** 51.0

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

**Notes:** by weight

**FLASHPOINT AND METHOD:** > 93.3°C (200°F)

**FLAMMABLE LIMITS:** Not Available to Not Available

**VAPOR PRESSURE:** 18 mmHg at (70.0°F)

**VAPOR DENSITY:** Not Determined

**BOILING POINT:** 100°C (212°F)

**FREEZING POINT:** 4.4°C (40.0°F)

**MELTING POINT:** Not Determined

**POUR POINT:** Not Determined

**SOLUBILITY IN WATER:** Miscible

**PARTITION COEFFICIENT: N-OCTANOL/WATER:** Not Determined

**EVAPORATION RATE:** > 1.0 (n-Butyl Acetate=1)

**DENSITY:** 9.00 lbs/gal

**PARTICLE SIZE:** Not Determined

**SPECIFIC GRAVITY:** 1.08

**VISCOSITY:** Not Determined

**MOLECULAR WEIGHT:** Not Determined

**(VOC):** 67 gr/L EPA Method 24 VOC

**OXIDIZING PROPERTIES:** Not Determined

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.

**STABILITY:** Stable.

**CONDITIONS TO AVOID:** Avoid exposure to high temperature. Avoid heat, sparks and flame.

**POSSIBILITY OF HAZARDOUS REACTIONS:** None Expected.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon dioxide, carbon monoxide, oxides of nitrogen, nitric acid, ammonia

**INCOMPATIBLE MATERIALS:** Mineral acids, oxidizing agents, sodium hypochlorite, peroxides

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

| Chemical Name | ORAL LD <sub>50</sub> (rat) | DERMAL LD <sub>50</sub> (rabbit) | INHALATION LC <sub>50</sub> (rat) |
|---------------|-----------------------------|----------------------------------|-----------------------------------|
| Polyamines    | 6700 mg/kg (rats)           | > 2000 mg/kg (rabbits)           | > 10 mg/L (1-hr dose)             |
| Acetic Acid   | No data                     | > 5000 mg/kg (rabbits)           | 5620 ppm (1-hr dose)              |

**SERIOUS EYE DAMAGE/IRRITATION:** Eyes, nose, throat, respiratory tract irritation.

### 12. ECOLOGICAL INFORMATION

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1

## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

**ENVIRONMENTAL DATA:** This product contains components that may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

**ECOTOXICOLOGICAL INFORMATION:** Contains components that are potentially toxic to freshwater and saltwater ecosystems.

**BIOACCUMULATION/ACCUMULATION:** No information for bioaccumulation is available.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not Regulated

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Regulated

#### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Not Regulated

### 15. REGULATORY INFORMATION

#### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

#### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

| Chemical Name | Wt. % | CERCLA RQ |
|---------------|-------|-----------|
| Acetic Acid   | < 1   | 5,000     |

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

| Chemical Name | CAS     |
|---------------|---------|
| Acetic Acid   | 64-19-7 |

#### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

### 16. OTHER INFORMATION

**Date Revised:** 09/06/2017

**INFORMATION CONTACT:** (714) 898-0025

# SAFETY DATA SHEET

**Date Prepared :** 09/06/2017  
**MSDS No :** PP EPP-WB B  
**Date Revised :** 09/06/2017  
**Revision No :** 1


## PACIFIC POLYMERS Elasto-Poxy Primer (Waterbase) Component B

**REVISION SUMMARY:** This MSDS replaces the 03/31/2015 MSDS. Revised: **Section 1:** Date Issued.

### HMIS RATING

|                            |   |          |
|----------------------------|---|----------|
| <b>HEALTH</b>              | * | <b>2</b> |
| <b>FLAMMABILITY</b>        |   | <b>1</b> |
| <b>PHYSICAL HAZARD</b>     |   | <b>0</b> |
| <b>PERSONAL PROTECTION</b> |   | <b>B</b> |

### NFPA CODES



**GENERAL STATEMENTS:** Keep out of reach of children  
 For professional or industrial use only

**MANUFACTURER DISCLAIMER:** This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.