

### PACIFIC POLYMERS ® “Primers at a Glance”

#### **Elasto-Poxy Primer VOC**

Excellent for concrete, metal/metal flashing, plywood or for damp substrates.

Will work with all of our Deck/Membranes systems 5000, 6500 including Elasto-Deck BT, Elasto-Mat D&G, Elasto-Deck BT H2O or as an inter-coat or re-coat primer.

#### **Elasto-Poxy Primer W.B.**

Low odor, interior or exterior, wood or concrete substrates.

Not for use on metal/metal flashing, nor as an inter-coat or re-coat primer.

Not for use with Elasto-Deck BT, Elasto-Mat D&G, Elasto-Deck BT H2O.

Note: Longer curing time required with colder temperatures.

#### **Deckthane Primer**

Single component, good for wood or concrete substrates.

Not for use on metal/metal flashing, nor as an inter-coat or re-coat primer for 5000 or 6500 deck systems.

However, it works very well with Elasto-Deck BT, Elasto-Mat D&G and Elasto-Deck BT H2O as a substrate or inter-coat/re-coat primer.

Longer curing time required with colder temperatures.

#### **IMPAX MMP Primer** (Manufactured by ITW Engineered Polymers)

Two component “Moisture mitigating” primer vapor drive primer (Up to 15 lbs.) can also be used as a “Low odor” inter-coat primer.

Please consult the product data sheets, SDS’s and your sales representative for specific project applications.



Acryl-R®

Permathane®



---

ITW Polymers Sealants North America

111 S. Nursery Road. Irving, TX

Tel 1-800-878-7876

International 972-438-9111

Fax 972-554-3939

[www.itwpsna.com](http://www.itwpsna.com)