

COLOR CHART



CONCRETE GRAY



TAN



ALOHA BROWN



ALUMINUM GRAY



BAJA BROWN




BRONZE



DESERT SAND



DRIFTWOOD



FALCON GRAY



FLINT GRAY



FOREST GREEN



GRANITE BROWN



LIMESTONE



PUMICE




RELISH



SADDLE



SMOKE GRAY



WHITE



WILSON BLUE



WINGTIP GRAY

The actual colors of Elasto-Glaze 6001ALHT Top Coat may vary slightly from the colors shown on the chart. This guide offers a representation of color. When matching is critical, a cured or applied color sample is highly recommended. Color matching available upon request.

PRODUCT GUIDE



ELASTO-POXY PRIMER (VOC)	Two component, solvent based VOC compliant epoxy resin based primer for use with the ELASTO-DECK 5000, ELASTO-DECK 6500 and ELASTO-DECK BT Systems. Also for re-coats, plywood, concrete and metal substrates.
ELASTO-POXY PRIMER W.B.	Low odor, two component water based epoxy primer for use with Elasto-Deck 5000 polyurethane based deck coating systems and Elasto-Deck 6500 traffic coating systems.
DECK-THANE PRIMER	Single component, moisture-cured, solvent-borne, VOC compliant polyurethane primer for concrete and wood surfaces.
ELASTO-DECK 5001NG	Liquid applied, single component, aromatic moisture-cured polyurethane membrane. Non-gassing.
ELASTO-DECK 5001HT	Liquid applied, single component, moisture-cured polyurethane, high tensile polyurethane membrane.
ELASTO-GLAZE 6001ALHT	Single component, high strength, aliphatic moisture-cured wear top coat sealer.
ELASTO-DECK 6500	Two component, aliphatic, high solids, low odor elastomeric traffic coating membrane for pedestrian or vehicular traffic.
ELASTO-DECK BT	Black, modified, liquid applied single component, moisture-cured polyurethane waterproofing coating, designed to form a seamless, flexible rubber membrane impervious to moisture.
ELASTO-DECK BT H2O	Unique, water cured modified polyurethane membrane for “one day” horizontal applications.
ELASTO-MAT D&G	Single component, fluid applied elastomeric waterproofing membrane for “damp and green” concrete.
ELASTO-DECK 5500	Liquid applied, single component, moisture-cured polyurethane membrane for waterproofing beneath tiles.
PERMATHANE® SM7108	Single component, multi-purpose, gun-grade, non-sag, moisture-cured polyurethane sealant.
ELASTO-THANE 227/227R	Two-part, gun-grade, non-staining, polyurethane sealant which cures to a firm, flexible rubber.
ELASTO-THANE 200	Two-part, cold applied, self-leveling jet fuel resistant polyurethane joint sealant which cures to a soft, flexible tear-resistant rubber (conforms to Federal Specification SS-S-200E).
ELASTO-SEAL 200	Two-part, cold applied, self-leveling, jet fuel resistant polysulfide joint sealant which cures to a soft, flexible tear-resistant rubber (conforms to Federal Specification SS-S-200E).
ERSYSTEMS® QUICKET	Multi-component, high solid, polyurethane elastomeric binder adhesive system used for correcting slope and ponding issues for deck and roofing applications.

REV 01.17